

TWL-System Data File Format Rules

An Explanation of the Data File Format

2008/05/30

**The content of this document is highly confidential
and should be handled accordingly.**

Confidential

These coded instructions, statements, and computer programs contain proprietary information of Nintendo and/or its licensed developers and are protected by national and international copyright laws. They may not be disclosed to third parties or copied or duplicated in any form, in whole or in part, without the prior written consent of Nintendo.

Table of Contents

1	Introduction	6
2	XML File Rules.....	7
2.1	XML File Structure.....	7
2.1.1	XML Declaration	7
2.1.2	The root Element.....	7
2.1.3	The head Element	7
2.1.4	The create Element	7
2.1.5	The title Element	8
2.1.6	The comment Element	8
2.1.7	The generator Element.....	8
2.1.8	The body Element	8
2.2	Example of an XML File	9
3	Binary File Rules.....	10
3.1	Binary File Structure.....	10
3.1.1	Header Part	10
3.1.2	Data Part	10
3.2	Binary File Header	11
3.2.1	The signature Parameter.....	11
3.2.2	The byteOrder Parameter	11
3.2.3	The version Parameter.....	11
3.2.4	The fileSize Parameter.....	11
3.2.5	The headerSize Parameter	12
3.2.6	The dataBlocks Parameter.....	12
3.3	Data Block Header	12
3.3.1	The kind Parameter	12
3.3.2	The size Parameter	12

Codes

Code 2-1	Example of an XML File	9
----------	------------------------------	---

Tables

Table 2-1	The head Element.....	7
Table 2-2	The create Element.....	8
Table 2-3	The generator Element	8
Table 3-2	Data Block Header	12

Figures

Figure 3-1 Binary File Structure.....	10
---------------------------------------	----

Revision History

Revision Date	Description
2008/05/30	Made revisions in line with the NITRO-System name change (from NITRO-System to TWL-System).
2008/04/08	Changed the format of the Revision History and revised the document.
2004/05/11	Initial version.

1 Introduction

TWL-System has a set of rules for the format of data files that are output by the tools. This document explains these file format rules.

2 XML File Rules

XML is being increasingly utilized for text-formatted data files to facilitate the handling of text-formatted data. TWL-System has a set of rules regarding the use of the XML format for text files. The XML-formatted text files that are supplied with TWL-System follow these rules.

2.1 XML File Structure

The TWL-System XML documents have a basic structure that stores one `head` element and one `body` element in the `root` element and the information that should be stored in the `head` element. The information for the body of the document is defined for each file format, and stored in the `body` element.

XML documents defined in TWL-System contain the elements described below. Except where it is stated, the order of these elements and the attributes inside these elements are not defined. The element tags must be checked and processed in order to interpret the XML document.

2.1.1 XML Declaration

XML files begin with the XML declaration. This declaration ensures that the XML processor correctly processes the written contents as an XML document.

2.1.2 The root Element

The `root` element describes the name of the document. The `root` element has one `version` attribute that describes the document's version. Also included inside the `root` element is one `head` element and one `body` element, stored in this respective order.

2.1.3 The head Element

The `head` element stores information that pertains to the overall document, including the creator, the time of creation, and comments. The head element also stores the following four elements:

Table 2-1 The head Element

Element	Description
<code>create</code>	Information that relates to the creation of the document.
<code>title</code>	The document title.
<code>comment</code>	Comments about the document.
<code>generator</code>	Information that relates to the generator.

2.1.4 The create Element

The `create` element stores information regarding the creation of the document. This element has only the four attributes shown below, and there are no contents.

Table 2-2 The create Element

Attribute	Description
user	Creator.
host	Name of machine used for creation.
date	The time of creation, expressed in the format: YYYY-MM-DDThh:mm:ss. This is an ISO8601 format, an expanded format that gives the date and the local time. (Example: 2002-01-17T17:03:00)
source	If there is source data, this attribute represents the string that indicates the data. The <i>create</i> element will not have this attribute if the document is newly created.

2.1.5 The title Element

The `title` element stores the title of the document (character data).

2.1.6 The comment Element

The `comment` element stores comments (character data) about the document. This is an optional element.

2.1.7 The generator Element

The `generator` element stores information that relates to the document's generator. The element has only the following two attributes, and there is no content. If the document has been mechanically created by the application, this element always exists.

Table 2-3 The generator Element

Attribute	Description
name	Generator name
version	Generator version

2.1.8 The body Element

The `body` element stores information about the overall document. The contents are defined for each data format type.

2.2 Example of an XML File

Here is an example of an XML document defined in TWL-System.

Code 2-1 Example of an XML File

```
<?xml version="1.0" encoding="Shift-JIS"?>

<sample version="1.0">

  <head>
    <create user="UserName" host="HostName" date="2002-01-18T10:15:00" source="s.xml"
  />
    <title>TWL-System XML</title>
    <comment>Example XML document </comment>
    <generator name="ToolName" version="1.0" />
  </head>

  <body>
    <!-- The content here is defined for each data format -->
  </body>

</sample>
```

3 Binary File Rules

TWL-System also has rules for binary files, which tend to be relatively large. The rules described here relate to the basic parts of the binary file structure. The rules governing the data contents depend on the various binary file formats.

3.1 Binary File Structure

Binary files are divided into two components (a header part and a data part), as shown in the figure below. In the binary file structure, the header part is always stored first. The data part that follows the header part stores data blocks that contain various types of binary data.

Figure 3-1 Binary File Structure

Binary File Header	Header Part
Data block 1	Data part
Data block 2	
Data block 3	
.	

3.1.1 Header Part

The header part stores a single binary file header that is at least 16 bytes in size. This binary file header stores information for identifying the type of the binary file. Information that is unique to each binary file format can be added to this binary file header. The size of this header must be 4-byte aligned.

3.1.2 Data Part

The data part stores a number of data blocks. An 8-byte data block header sits at the start of each data block. Data blocks are only defined to have the data block header at the start the data block, and the data block contents are defined for each type of binary data format.

The size of each data block must at least be 4-byte aligned. Depending on the rules for the various binary file formats, the data block size may be aligned in a larger unit. Moreover, the order in which data blocks are stored is defined for each binary file format type. (Whether the data blocks are arranged in unspecified or specified order varies depending on the type of the binary file format.)

3.2 Binary File Header

The structure of the binary file header is shown in the following table. The binary file header is at least 16 bytes in size. The binary file header stores the signature indicating the binary file type, and its version number, as well as the code for determining the endian method, binary file size, and number of data blocks contained in the binary file.

Table 3-1 Binary File Header

Type	Parameter Name	Meaning	Size
char[4]	signature	File signature	4 bytes
u16	byteOrder	Byte-order mark (for determining endian method)	2 bytes
u16	version	Binary file format's version number	2 bytes
u32	fileSize	Size of binary file	4 bytes
u16	headerSize	Size of binary file header	2 bytes
u16	dataBlocks	Number of data blocks	2 bytes

3.2.1 The signature Parameter

The `signature` parameter stores the file signature, which determines the binary file type.

This file signature is a 4-byte code that is stored in memory in order from the highest bit, regardless of the endian method. Note that all other data is dependent on the endian method.

This file signature is stored as four ASCII characters and managed to avoid duplication among the different binary file types.

3.2.2 The byteOrder Parameter

The `byteOrder` parameter stores the byte order mark (Zero Width No Break Space, `0xfeff`) that is used to determine the endian method. The byte data string is stored in order of `0xfe`, `0xff` for big-endian and `0xff`, `0xfe` for little-endian.

Binary files for TWL and Nintendo DS are created using the little-endian method. The information is set in consideration of cases where the same file format is shared with game machines that use a different byte order.

3.2.3 The version Parameter

The `version` parameter stores the binary file format's version number. The upper byte stores the major version (integral value), while the lower byte stores the minor version (decimal value). Thus, the version number 1.2 would be the value `0x0102`.

3.2.4 The fileSize Parameter

The `fileSize` parameter stores the total size of the binary file, including the binary file header.

3.2.5 The headerSize Parameter

The `headerSize` parameter stores the size of the binary file header. The size of the binary file header is prescribed to be 16 bytes. Therefore, a value 16 is normally stored. If the binary file header stores information that is unique to the different binary file formats, `headerSize` stores the total size, including this unique information. The size of binary file header must be 4-byte aligned.

The very first data block that is included in the binary file is positioned away from the start of the binary file (binary header) by the exact number of bytes that is specified in `headerSize`.

3.2.6 The dataBlocks Parameter

The `dataBlocks` parameter stores the number of data blocks that are included in the data part of the binary file. The `dataBlocks` value is an unsigned 16-bit value. One binary file can store up to 65,535 data blocks.

3.3 Data Block Header

Each data block in the data part of the binary file starts with a data block header that has the structure shown below. The data block header is 8 bytes in size, and it stores the type and size of the data block.

Table 3-2 Data Block Header

Type	Parameter Name	Meaning	Size
u32	kind	Data block type	4 bytes
u32	size	Data block size	4 bytes

3.3.1 The kind Parameter

The `kind` parameter stores a 4-byte code that describes the data block type. The codes are prescribed for each binary file format. In other words, if the binary file signatures are different, the contents of the two blocks will differ even if they both have the same value for `kind`. Normally data block kinds are composed of four ASCII characters.

3.3.2 The size Parameter

The `size` parameter stores the size of the data block, including the data block header. The size of the data block must be a value that is 4-byte aligned.

If there are more than one data block, each successive data block is positioned away from the preceding data block header by the exact number of bytes that are specified in `size`.

All company and product names in this document are the trademarks or registered trademarks of the respective companies.

© 2004-2009 Nintendo

The contents of this document cannot be duplicated, copied, reprinted, transferred, distributed, or loaned in whole or in part without the prior approval of Nintendo.